

Non-Catalog Model

Frequency Mixer

SRA-2010MH

Level 13 (LO Power +13 dBm)

Important Note

This is a non-catalog model and can be manufactured on specific request. Pricing and delivery information can be supplied upon request.

Please click "Back", and then click "Contact Us" for Applications support.



CASE STYLE : A06

ELECTRICAL SPECIFICATIONS 50Ω @ +25°C					
Parameter		Min.	Typ.	Max.	Units
Frequency	LO (fL to fU)	10		2000	MHz
	RF (fL to fU)	10		2000	MHz
	IF	0		600	MHz
Conversion Loss	mid band		7.5	8.5	dB
	Total Range			9.8	dB
LO-RF Isolation	Low Range	45	50		dB
	Mid Range	30	45		dB
	Upper Range	25	40		dB
LO-IF Isolation	Low Range	40	45		dB
	Mid Range	30	35		dB
	Upper Range	20	35		dB
1 dB Comp. Input Power			+9		dBm

Notes: Low Range = [fL to 10fL]
mid band = [2fL to fU/2]

Mid Range = [10fL to fU/2]

Upper Range = [fU/2 to fU]

Hermetically sealed

MAXIMUM RATINGS	
Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power	200mW
IF Current	40mA

PIN CONNECTIONS	
LO	8
RF	1
IF	3
GROUND	2, 5, 6, 7

Electrical Schematics

